

## DECLARATION OF PERFORMANCE IN ACCORDANCE WITH CONSTRUCTION PRODUCTS GUIDELINE

### NR. 003

<b>1. Identification code of product type:</b>	Ceramic tiles, extruded with low water absorption $E_b \leq 0,5\%$ , group BI <sub>a</sub> attachment G, glazed (GL) and unglazed (UGL)
<b>2. Intended use:</b>	For indoor and outdoor floorings and wall coverings
<b>3. Manufacturer:</b>	Ströher GmbH, Ströherstraße 2-10, 35683 Dillenburg
<b>4. System(s) of assessment and verification of constancy of performance in accordance with attachment V:</b>	System 4
<b>5. Harmonized standard:</b>	DIN EN 14411: 2012
<b>6. DECLARED PERFORMANCES:</b>	

Essential characteristics	Performance
Reaction to fire	A1 / A1 <sub>FL</sub>
<b>Release of hazardous substances:</b>	
- Cadmium	NPD
- Lead	NPD
- Others	NPD
<b>Durability for:</b>	
- Indoor use	passed
- Outdoor use: resistance to freeze thaw cycles	passed
<b>Breaking load</b>	Thickness $\geq 7,5$ mm: $\geq 1.300$ N Thickness $< 7,5$ mm: $\geq 700$ N
<b>Slip resistance properties</b>	
CEN/TS 16165 attachment A	NPD
<b>Tactility</b>	NPD
<b>Bending strength/adhesion:</b>	
- Cementitious mortar, type C1	$\geq 0,5$ N/mm <sup>2</sup>
- Dispersion adhesives	NPD
- Reaction resin adhesives	NPD
- Mortar	NPD
<b>Thermal shock resistance</b>	passed

7. The performances of the above mentioned product correspond to the declared performances. This declaration of performance was issued in accordance with (EU) Regulation No. 305/2011 under the sole responsibility of the manufacturer stated above. Signed for and on behalf of the manufacturer by:

Patrick Schneider (Geschäftsführer)

Name und Funktion

Dillenburg, 15.10.2020

Ort und Datum der Ausstellung



Unterschrift

**Ströher GmbH**  
Ströherstraße 2-10  
35683 Dillenburg  
Telefon: +49 2771 391-0  
Telefax: +49 2771 391-340  
E-Mail: info@stroeher.de  
Internet: www.stroeher.de