

DECLARATION OF PERFORMANCE IN ACCORDANCE WITH CONSTRUCTION PRODUCTS GUIDELINE

NR. 006

1. Identification code of product type:

- 2. Intended use:
- 3. Manufacturer:
- 4. System(s) of assessment and verification of constancy of performance in accordance with attachment V:

5. Harmonized standard:

System 4

Ceramic tiles, extruded with low water absorption

Ströher GmbH, Ströherstraße 2-10, 35683 Dillenburg

 $E_{h} \leq 0.5\%$, group Bl_a attachment G, glazed (GL) and unglazed (UGL)

For indoor and outdoor wall coverings

DIN EN 14411: 2012

6. DECLARED PERFORMANCES:

Essential characteristics Performance Reaction to fire A1 Release of hazardous substances: - Cadmium NPD - Lead NPD - Others NPD **Durability for:** - Indoor use passed - Outdoor use: resistance to freeze thaw cycles passed Breaking load Thickness ≥ 7,5 mm: > 1.300 N Bending strength/adhesion: - Cementitious mortar, type C1 ≥ 0,5 N/mm² - Dispersion adhesives NPD NPD - Reaction resin adhesives - Mortar NPD Thermal shock resistance passed

7. The performances of the above mentioned product correspond to the declared performances. This declaration of performance was issued in accordance with (EU) Regulation No. 305/2011 under the sole responsibility of the manufacturer stated above. Signed for and on behalf of the manufacturer by:

	Patrick Schneider (Geschäftsführer)	\bigcirc	
Dillenburg, 21.04.2023 Ort und Datum der Ausstellung	Name und Funktion	Π.	Ströher GmbH Ströherstraße 2-10 35623 Dillenburg Telefon: +49 2771 391-0 Unterschriffelefax: +49 2771 391-340 E-Mail: info@stroeher.de

Internet: www.stroeher.de