

## **DECLARATION OF PERFORMANCE** IN ACCORDANCE WITH CONSTRUCTION PRODUCTS GUIDELINE

## ND OOG

Dillenburg, 21.04.2023

. Identification code of product type:	Ceramic tiles, extruded with low water absorption $E_b \le 0.5\%$ , group $Bl_a$ attachment G, glazed (GL) and unglazed (UGL)
2. Intended use:	For indoor and outdoor wall coverings
3. Manufacturer:	Ströher GmbH, Ströherstraße 2-10, 35683 Dillenburg
<ul> <li>System(s) of assessment and verification of constancy of performance in accordance with attachment V:</li> </ul>	System 4
5. Harmonized standard:	DIN EN 14411: 2012
6. DECLARED PERFORMANCES:	
Essential characteristics	Performance
Reaction to fire	A1
Release of hazardous substances:	
- Cadmium	NPD
- Lead	NPD
- Others	NPD
Durability for:	
- Indoor use	passed
- Outdoor use: resistance to freeze thaw cycles	passed
Breaking load	Thickness ≥ 7,5 mm: > 1.300 N
Bending strength/adhesion:	
- Cementitious mortar, type C1	≥ 0,5 N/mm²
- Dispersion adhesives	NPD
- Reaction resin adhesives	NPD
– Mortar	NPD
Thermal shock resistance	passed

Telefon: +49 2771 391-0 Unterschriffelefax: +49 2771 391-340 Ort und Datum der Ausstellung E-Mail: info@stroeher.de Internet: www.stroeher.de