

DECLARATION OF PERFORMANCE IN ACCORDANCE WITH CONSTRUCTION PRODUCTS GUIDELINE

Nr. 005

- | | |
|--|--|
| 1. Identification code of product type: | Ceramic tiles, extruded with low water absorption
$0,5\% < E_w \leq 3\%$, group BI _a attachment H,
glazed (GL) |
| 2. Intended use: | For indoor and outdoor floorings and wall coverings |
| 3. Manufacturer: | Ströher GmbH, Ströherstraße 2-10, 35683 Dillenburg |
| 4. System(s) of assessment and verification of constancy of performance in accordance with attachment V: | System 4 |
| 5. Harmonized standard: | DIN EN 14411:2016 |
| 6. DECLARED PERFORMANCES: | |

Essential characteristics

Reaction to fire

Release of hazardous substances:

– Cadmium

– Lead

– Others

Durability for:

– Indoor use

– Outdoor use: resistance to freeze thaw cycles

Breaking load

Slip resistance properties

CEN/TS 16165 attachment A

Tactility

Bending strength/adhesion:

– Cementitious mortar, type C1

– Dispersion adhesives

– Reaction resin adhesives

– Mortar

Thermal shock resistance

Performance

A1 / A1_{FL}

NPD

NPD

NPD

passed

passed

Thickness $\geq 7,5$ mm: ≥ 1.100 N

NPD

NPD

$\geq 0,5$ N/mm²

NPD

NPD

NPD

passed

7. The performances of the above mentioned product correspond to the declared performances. This declaration of performance was issued in accordance with (EU) Regulation No. 305/2011 under the sole responsibility of the manufacturer stated above. Signed for and on behalf of the manufacturer by:

Dirk Hümmer (Geschäftsführer)

Name und Funktion

Dillenburg, 15.10.2020

Ort und Datum der Ausstellung

Ströher GmbH

Ströherstraße 2-10

35683 Dillenburg

Telefon: +49 2771 391-0

Telefax: +49 2771 391-340

E-Mail: info@stroeher.de

Internet: www.stroeher.de

Unterschrift