

DECLARATION OF PERFORMANCE IN ACCORDANCE WITH CONSTRUCTION PRODUCTS GUIDELINE

Nr. 003

- | | |
|---|---|
| 1. Identification code of product type: | Ceramic tiles, extruded with low water absorption
$E_b \leq 0,5\%$, group BI _a attachment G,
glazed (GL) and unglazed (UGL) |
| 2. Intended use: | For indoor and outdoor floorings and wall coverings |
| 3. Manufacturer: | Ströher GmbH, Ströherstraße 2-10, 35683 Dillenburg |
| 4. System(s) of assessment and verification of constancy of performance in accordance with attachment V: | System 4 |
| 5. Harmonized standard: | DIN EN 14411:2016 |
| 6. DECLARED PERFORMANCES: | |

Essential characteristics	Performance
Reaction to fire	A1 / A1 _{FL}
Release of hazardous substances:	
– Cadmium	NPD
– Lead	NPD
– Others	NPD
Durability for:	
– Indoor use	passed
– Outdoor use: resistance to freeze thaw cycles	passed
Breaking load	Thickness $\geq 7,5$ mm: ≥ 1.300 N Thickness $< 7,5$ mm: ≥ 700 N
Slip resistance properties	
CEN/TS 16165 attachment A	NPD
Tactility	NPD
Bending strength/adhesion:	
– Cementitious mortar, type C1	$\geq 0,5$ N/mm ²
– Dispersion adhesives	NPD
– Reaction resin adhesives	NPD
– Mortar	NPD
Thermal shock resistance	passed


- 7.** The performances of the above mentioned product correspond to the declared performances. This declaration of performance was issued in accordance with (EU) Regulation No. 305/2011 under the sole responsibility of the manufacturer stated above. Signed for and on behalf of the manufacturer by:

Patrick Schneider (Geschäftsführer)

Name und Funktion

Dillenburg, 15.10.2020

Ort und Datum der Ausstellung


Ströher GmbH
 Ströherstraße 2-10
 35683 Dillenburg
 Telefon: +49 2771 391-0
 Telefax: +49 2771 391-340
 E-Mail: info@stroehher.de
 Internet: www.stroehher.de

Unterschrift